

### PRELIMINARY AIR MONITORING SUMMARY

Jenkintown, PA SPS Technologies Fire March 7 – 8, 2025

Submitted March 9, 2025

### **1.0 INTRODUCTION**

On February 19, 2025, CTEH was contacted to provide community air monitoring for SPS Technologies, LLC in conjunction with the United States Environmental Protection Agency (USEPA) and the Pennsylvania Department of Environmental Protection (PA DEP). CTEH initially established seven stationary real-time air monitoring locations in a perimeter around the SPS Technologies facility and adjacent residential areas on the morning of February 20, 2025. Real-time air monitoring performed by CTEH began at 1208 EST on February 20, 2025. At 1000 EST on February 22, 2025, CTEH established a Kestrel 6000 cellular weather station approximately 500 feet north of the facility. On the evening of February 22, 2025, CTEH established four additional stationary monitoring locations in community areas around the facility. Consistent with the updated Air Sampling and Analysis Plan (SAP) submitted on February 23, 2025, CTEH established two additional community stationary monitoring locations on both February 23 and February 24, 2025, bringing the total number of stationary monitoring locations to fifteen. The SAP was further updated on February 26, 2025 to reflect the removal of particulate matter monitors during rain events and a change in how monitoring stations were identified. These stationary real-time monitoring locations were established to encompass a 360° monitoring perimeter around the facility and within nearby communities.

This report summarizes real-time air monitoring data collected by CTEH personnel from approximately 0600 EST on March 7, 2025 to approximately 0600 EST on March 8, 2025.

### 2.0 AIR MONITORING METHODS

Real-time air monitoring refers to the use of direct-reading instruments to provide a near-instantaneous readout of chemical concentrations in the air. On February 19, 2025, CTEH personnel developed a SAP to document and quantify the potential release of fugitive emissions from the incident. CTEH has continued to update the SAP and associated monitoring locations based on feedback from PA DEP. The analytes chosen for air monitoring were coordinated with representatives from USEPA and PA DEP for this incident based on the Tier II documentation for the SPS Technologies Facility.

Handheld real-time air monitoring refers to data collected by roaming CTEH personnel using handheld air monitoring instruments. Stationary real-time air monitoring refers to stationary instruments that record air monitoring data approximately every 15 seconds and send the data in real time to a centralized location via radio telemetry. Handheld and Stationary real-time air monitoring were conducted using RAE<sup>®</sup> Systems by Honeywell MultiRAE Pro and AreaRAE instruments equipped with 10.6 eV photoionization detectors and multiple electrochemical sensors, ChemLogic CLPx portable gas detectors, and Gastec GV-100 pumps equipped with chemical-specific, colorimetric detector tubes. These include volatile organic compounds (VOCs), hydrogen cyanide (HCN), hydrogen sulfide (H<sub>2</sub>S), chlorine (Cl<sub>2</sub>), carbon



monoxide (CO), sulfuric acid, nitric acid, and flammability as a percentage of the lower explosive limit (%LEL). Additionally, handheld and stationary real-time air monitoring for particulate matter of 2.5  $\mu$ m diameter or less (PM<sub>2.5</sub>) was conducted using TSI SidePak AM520 instruments.

Stationary air monitoring equipment is subject to drift events, which are defined as any interference in an instrument's photoionization detector (PID; 10.6 eV) or electrochemical sensor's ability to accurately report the concentration of a chemical in the atmosphere. Common sources of drift include impacts from humidity, temperature changes, and issues with instrument batteries. These drift sources may cause air monitoring equipment to report consistent, low-level detections in the absence of chemicals present in the air.

In total, CTEH has established fifteen stationary real-time air monitoring locations as part of this response. Six air monitoring stations were installed around the perimeter of the impacted facility. The remaining nine monitoring stations were established in the communities surrounding the impacted facility, including schools and parks. These locations include Baederwood Park, the Glenside Youth Athletic Club Baseball Fields, the Noble Train Station, Jenkintown Middle/High School, Salus University, Thomas Williams Park, Curtis Arboretum, Arcadia University, and Glenn Memorial Hall.

### 3.0 AIR MONITORING RESULTS

Maps of the incident location, real-time air monitoring results, and the locations of stationary real-time air monitoring locations are provided in **Attachment A**. The results of handheld real-time air monitoring are summarized in **Table 1**. The results of stationary real-time air monitoring from the perimeter locations are summarized in **Tables 2 and 3**. The results of the stationary real-time air monitoring from the community locations are summarized in **Tables 4 and 5**. Visual depictions of the stationary real-time air monitoring data from the perimeter locations are provided in **Attachment B**. Visual depictions of the stationary real-time air monitoring data from the perimeter locations are provided in **Attachment B**. Visual depictions of the stationary real-time air monitoring data from the community locations are provided in **Attachment C**. A wind rose depicting wind direction and wind speed during this reporting period is provided in **Attachment D**. Meteorological data were acquired from both the PHILADELPHIA NE weather station in Philadelphia, PA, and a Kestrel 6000 cellular weather station located approximately 500 feet north of the facility.



#### 3.1 Handheld Real-Time Air Monitoring Results

Analyte	Instrument	Number of Readings	Number of Detections	Concentration Range*
Cl <sub>2</sub>	CLPx	119	0	< 1 ppb
	MultiRAE	29	0	< 0.1 ppm
Nitric Acid	Gastec #15L	190	0	< 0.05 ppm
Sulfuric Acid	CLPx	63	0	< 23.3 ppb
	Gastec #35	129	0	< 0.2 mg/m <sup>3</sup>

#### Table 1: Handheld Real-Time Perimeter and Expanded Community Air Monitoring Results<sup>+</sup>

<sup>+</sup>Note: This is a preliminary data summary, indicating that the data provided has not undergone full quality assurance and quality control (QAQC) process and should be considered preliminary at this time.

\*If no detectable concentration was observed, the instrument detection limit is preceded by a "<" symbol.

There were no detections of any analyte evaluated during Handheld Perimeter Air Monitoring or Handheld Community Air Monitoring in this reporting period.

#### 3.2 Stationary Real-Time Perimeter Air Monitoring Results

#### Table 2. Summary of Stationary Real-Time Perimeter Air Monitoring AreaRAE Results<sup>+</sup>

Unit	Analyte	Number of Readings	Number of Detections	Concentration Range*
	СО	5,782	0	< 1.0 ppm
	$H_2S$	5,784	0	< 0.1 ppm
Station 01	HCN	5,784	0	< 1.0 ppm
	%LEL	5,784	0	< 1.0 %
	VOCs	5,784	906	0.1 - 0.2 ppm
	CO	5,787	0	< 1.0 ppm
	$H_2S$	5,787	0	< 0.1 ppm
Station 03	HCN	5,787	0	< 1.0 ppm
	%LEL	5,787	0	< 1.0 %
	VOCs	5,789	0	< 0.1 ppm
	CO	5,757	0	< 1.0 ppm
	$H_2S$	5,759	0	< 0.1 ppm
Station 04	HCN	5,759	0	< 1.0 ppm
	%LEL	5,759	0	< 1.0 %
	VOCs	5,759	631	0.1 ppm
	CO	5,770	0	< 1.0 ppm
Station 05	$H_2S$	5,738	0	< 0.1 ppm
	HCN	5,770	0	< 1.0 ppm

Preliminary Air Monitoring Summary SPS Technologies Fire March 7 - 8, 2025



	%LEL	5,770	0	< 1.0 %
-	VOCs	5,770	72	0.1 ppm
	CO	5,751	0	< 1.0 ppm
-	$H_2S$	5,751	0	< 0.1 ppm
Station 06	HCN	5,751	0	< 1.0 ppm
-	%LEL	5,751	0	< 1.0 %
-	VOCs	5,749	330	0.1 - 0.2 ppm
	CO	5,747	0	< 1.0 ppm
-	H <sub>2</sub> S	5,747	0	< 0.1 ppm
Station 07	HCN	5,747	0	< 1.0 ppm
-	%LEL	5,747	0	< 1.0 %
-	VOCs	5,747	164	0.1 ppm

<sup>†</sup>Note: This is a preliminary data summary, indicating that the data provided has not undergone full quality assurance and quality control (QAQC) process and should be considered preliminary at this time. AreaRAE monitoring data contains drift events. Drift is defined as any interference in an instrument's photoionization detector (PID; 10.6 eV) or electrochemical sensor's ability to accurately report the concentration of a chemical in the atmosphere. Humidity, rapid temperature changes, and compromised instrument batteries are examples of common sources of drift. \* If no detection was observed, the instrument detection limit preceded by a "<" symbol is listed; ppm = parts per million

Unit	Instrument	24-Hour PM <sub>2.5</sub> NAAQS	Average $PM_{2.5}$ Concentration (mg/m <sup>3</sup> )
Station 1	AM520	0.035	0.004
Station 3	AM520	0.035	0.004
Station 4	AM520	0.035	0.004
Station 5	AM520	0.035	0.003
Station 6	AM520	0.035	0.003
Station 7	AM520	0.035	0.004

#### Table 3: Summary of Stationary Real-Time Perimeter Air Monitoring PM<sub>2.5</sub> Results<sup>†</sup>

<sup>+</sup>Note: This is a preliminary data summary, indicating that the data provided has not undergone full quality assurance and quality control (QAQC) process and should be considered preliminary at this time.

During stationary real-time perimeter air monitoring, there were no detections of CO, H<sub>2</sub>S, HCN or %LEL at any air monitoring station. During this reporting period, PM<sub>2.5</sub> monitoring was paused at approximately 1935 EST on March 7, 2025 due to rain events per the SAP v1.2 addendum. There were no elevated average PM<sub>2.5</sub> concentrations observed in the perimeter monitoring locations during this reporting period.



Unit	Analyte	Count of Readings	Count of Detections	Range of Detections
	СО	4,862	6	2.0 - 9.0 ppm
	$H_2S$	4,862	0	< 0.1 ppm
Station 02	HCN	3,387	0	< 1.0 ppm
	LEL	4,862	0	< 1.0 %
	VOCs	4,862	149	0.1 - 0.2 ppm
	СО	4,994	0	< 1.0 ppm
	$H_2S$	4,994	0	< 0.1 ppm
Station 08	HCN	4,580	0	< 1.0 ppm
	LEL	4,994	0	< 1.0 %
	VOCs	4,994	33	0.1 ppm
	СО	5,280	0	< 1.0 ppm
	$H_2S$	5,280	0	< 0.1 ppm
Station 09	HCN	5,280	0	< 1.0 ppm
	LEL	5,280	0	< 1.0 %
	VOCs	5,280	0	< 0.1 ppm
	СО	5,144	0	< 1.0 ppm
	$H_2S$	5,144	0	< 0.1 ppm
Station 10	HCN	5,144	0	< 1.0 ppm
	LEL	5,144	0	< 1.0 %
	VOCs	5,144	0	< 0.1 ppm
	СО	5,173	0	< 1.0 ppm
	$H_2S$	5,173	0	< 0.1 ppm
Station 11	HCN	5,173	0	< 1.0 ppm
	LEL	5,173	0	< 1.0 %
	VOCs	5,173	765	0.1 ppm
	СО	5,337	0	< 1.0 ppm
	$H_2S$	5,337	0	< 0.1 ppm
Station 12	HCN	5,337	0	< 1.0 ppm
	LEL	5,337	0	< 1.0 %
	VOCs	5,337	1,325	0.1 - 0.2 ppn
	СО	5,404	3	2.0 - 14.0 ppm
Station 12	$H_2S$	5,404	0	< 0.1 ppn
Station 13	HCN	5,404	0	< 1.0 ppn
	LEL	5,404	0	< 1.0 %

### 3.3 Stationary Real-Time Expanded Community Air Monitoring Results

Table 3. Summary of Stationary Real-Time Expanded Community Air Monitoring AreaRAE Results<sup>†</sup>



	VOCs	5,404	135	0.1 ppm
	CO	4,818	0	< 1.0 ppm
-	$H_2S$	4,818	0	< 0.1 ppm
Station 14	HCN	4,818	0	< 1.0 ppm
•	LEL	4,818	0	< 1.0 %
-	VOCs	4,818	132	0.1 ppm
	CO	4,414	0	< 1.0 ppm
-	$H_2S$	4,414	0	< 0.1 ppm
Station 15	HCN	4,414	0	< 1.0 ppm
	LEL	4,414	0	< 1.0 %
-	VOCs	4,414	783	0.1 ppm

\*Note: This is a preliminary data summary, indicating that the data provided have not undergone full quality assurance and quality control (QAQC) process and should be considered preliminary at this time. AreaRAE monitoring data contain drift events. Drift is defined as any interference in an instrument's photoionization detector (PID; 10.6 eV) or electrochemical sensor's ability to accurately report the concentration of a chemical in the atmosphere. Humidity, rapid temperature changes, and compromised instrument batteries are examples of common sources of drift. \* If no detection was observed, the instrument detection limit preceded by a "<" symbol is listed; ppm = parts per million

Unit	Instrument	24-Hour PM <sub>2.5</sub> NAAQS	Average $PM_{2.5}$ Concentration (mg/m <sup>3</sup> )
Station 2	AM 520	0.035	0.003
Station 8	AM520	0.035	0.003
Station 9	AM520	0.035	0.004
Station 10	AM520	0.035	0.004
Station 11	AM520	0.035	0.005
Station 12	AM520	0.035	0.004
Station 13	AM520	0.035	0.003
Station 14	AM520	0.035	0.003
Station 15	AM520	0.035	0.004

#### Table 5: Summary of Stationary Real-Time Expanded Community Air Monitoring PM<sub>2.5</sub> Results<sup>†</sup>

<sup>†</sup>Note: This is a preliminary data summary, indicating that the data provided has not undergone full quality assurance and quality control (QAQC) process and should be considered preliminary at this time.

Stationary real-time monitoring at nine locations in communities surrounding the facility indicated no detections of  $H_2S$ , HCN, or % LEL. Transient, low-level detections of CO were observed at Stations 2 and 13. During this reporting period,  $PM_{2.5}$  monitoring was paused at approximately 1935 EST on March 7, 2025 due to a rain event per the SAP v1.2 addendum. There were no elevated average  $PM_{2.5}$  concentrations observed in the community monitoring locations during this reporting period.



### 3.4 Analyte-Specific Action Levels

As part of the SAP, air monitoring action levels were identified for air monitoring detections for which onsite incident management members should be notified. The action levels identified in the SAP are provided in **Table 6**.

		Action Levels					
Concentration Durations		Sustained for 5 Minutes	Sustained for 30 Seconds				
Analyte	CAS	Protective Action Criteria 1 (PAC-1)	½ Protective Action Criteria 2 (½ PAC-2)				
Sulfuric Acid	7664-93-9	0.05 ppm	1.1 ppm				
Nitric Acid	7697-37-2	0.16 ppm	12 ppm				
Hydrogen Cyanide	74-90-8	2 ppm	3.5 ppm				
Hydrogen Sulfide	7783-06-4	0.51 ppm	13.5 ppm				
Chlorine	7782-50-5	0.5 ppm	1.0 ppm				

#### Table 6: Analyte-Specific Action Levels Resulting in Stakeholder Notification

If any analyte exceeds the PAC-1 for 5 minutes and is confirmed with a secondary instrument or if any analyte exceeds ½ PAC-2 for 30 seconds, the CTEH monitoring personnel will immediately contact the CTEH Project Technical Director via a telephone call. The CTEH Project Technical Director will then notify a designated group of SPS representatives via group text message and individual phone calls for appropriate stakeholder notifications and emergency management decision-making.

During this reporting period, there were no action level exceedances of any analyte evaluated requiring notification of on-site incident management.

### 4.0 METEOROLOGICAL CONDITIONS

**Attachment D** contains wind roses depicting wind speed and direction from station PHILADELPHIA NE, approximately 6.89 miles from the site, and a Kestrel 6000 cellular monitoring station located approximately 500 feet north of the facility.




# Attachment A

Maps








Projection: NAD 1983 2011 StatePlane Pennsylvania South FIPS 3702 Ft US


Miles



Projection: NAD 1983 2011 StatePlane Pennsylvania South FIPS 3702

Feet

Updated At: 3/8/2025 10:02 AM




Projection: NAD 1983 2011 StatePlane Pennsylvania South FIPS 3702

0 1,000

Updated At: 3/8/2025 10:01 AM

Project: PROJ-052216



Projection: NAD 1983 2011 StatePlane Pennsylvania South FIPS 3702

Feet

Updated At: 3/8/2025 10:02 AM

## Attachment B

## Stationary Real-Time Perimeter Monitoring Graphs




Preliminary Fixed Station Real-time Air Monitoring Readings PROJ-052216 | SPS Technologies Fire | Abington Township, PA 3/7/2025 4:08:17 AM to 3/8/2025 4:06:56 AM | **Analyte: CO (ppm)** 




Local Time

Preliminary Fixed Station Real-time Air Monitoring Readings PROJ-052216 | SPS Technologies Fire | Abington Township, PA 3/7/2025 4:08:17 AM to 3/8/2025 4:06:56 AM | **Analyte: H2S (ppm)** 




Preliminary Fixed Station Real-time Air Monitoring Readings PROJ-052216 | SPS Technologies Fire | Abington Township, PA 3/7/2025 4:08:17 AM to 3/8/2025 4:06:56 AM | **Analyte: HCN (ppm)** 




03/07 05:00 03/07 07:00 03/07 09:00 03/07 11:00 03/07 13:00 03/07 15:00 03/07 17:00 03/07 19:00 03/07 21:00 03/07 23:00 03/08 01:00 03/08 03:00 03/08 05:00

Preliminary Fixed Station Real-time Air Monitoring Readings PROJ-052216 | SPS Technologies Fire | Abington Township, PA 3/7/2025 4:08:17 AM to 3/8/2025 4:06:56 AM | **Analyte: LEL (%)** 




Preliminary Fixed Station Real-time Air Monitoring Readings PROJ-052216 | SPS Technologies Fire | Abington Township, PA 3/7/2025 4:08:17 AM to 3/8/2025 4:06:56 AM | Analyte: VOCs (ppm)



03/07 05:00 03/07 07:00 03/07 09:00 03/07 11:00 03/07 13:00 03/07 15:00 03/07 17:00 03/07 19:00 03/07 21:00 03/07 23:00 03/08 01:00 03/08 03:00 03/08 05:00

### PROJ-052216 | PM2.5 Graph

SPS Technologies Fire | Abington Township, PA 03/07 05:17 to 03/07 19:59



### PROJ-052216 Summary Table | PM2.5


Unit	Particle Size	Count of Records	Count of Detections	Min. concentration	Max. concentration	Avg. concentration
Station 01	PM2.5	3,459	3,459	0.002	0.047	0.004
Station 03	PM2.5	3,501	3,501	0.002	0.024	0.004
Station 04	PM2.5	3,483	3,483	0.002	0.016	0.004
Station 05	PM2.5	3,488	3,488	0.001	0.009	0.003
Station 06	PM2.5	3,441	3,439	0.000	0.028	0.003
Station 07	PM2.5	3,484	3,484	0.002	0.096	0.004

# Attachment C


## Stationary Real-Time Community Monitoring Graphs




### Preliminary Fixed Station Real-time Air Monitoring Readings PROJ-052216 | Expanded Community | SPS Technologies Fire | Abington Township, PA 3/7/2025 6:00:00 AM to 3/8/2025 4:38:06 AM | **Analyte: CO (ppm)**




### Preliminary Fixed Station Real-time Air Monitoring Readings PROJ-052216 | Expanded Community | SPS Technologies Fire | Abington Township, PA 3/7/2025 6:00:00 AM to 3/8/2025 4:38:06 AM | **Analyte: H2S (ppm)**




### Preliminary Fixed Station Real-time Air Monitoring Readings PROJ-052216 | Expanded Community | SPS Technologies Fire | Abington Township, PA 3/7/2025 6:00:00 AM to 3/8/2025 4:38:06 AM | **Analyte: HCN (ppm)**



### Preliminary Fixed Station Real-time Air Monitoring Readings PROJ-052216 | Expanded Community | SPS Technologies Fire | Abington Township, PA 3/7/2025 6:00:00 AM to 3/8/2025 4:38:06 AM | **Analyte: LEL (%)**




### Preliminary Fixed Station Real-time Air Monitoring Readings PROJ-052216 | Expanded Community | SPS Technologies Fire | Abington Township, PA 3/7/2025 6:00:00 AM to 3/8/2025 4:38:06 AM | **Analyte: VOCs (ppm)**



### PROJ-052216 | PM2.5 Graph | Expanded Community

SPS Technologies Fire | Abington Township, PA 03/07 05:00 to 03/07 21:15



### PROJ-052216 Summary Table | PM2.5 | Expanded Community

Unit	Particle Size	Count of Records	Count of Detections	Min. concentration	Max. concentration	Avg. concentration
Station 02	PM2.5	3,477	3,477	0.001	0.009	0.003
Station 08	PM2.5	3,493	3,493	0.001	0.012	0.003
Station 09	PM2.5	3,744	3,744	0.002	0.019	0.004
Station 10	PM2.5	3,469	3,469	0.002	0.010	0.004
Station 11	PM2.5	3,691	3,691	0.002	0.039	0.005
Station 12	PM2.5	3,775	3,775	0.001	0.024	0.004
Station 13	PM2.5	3,880	3,880	0.001	0.012	0.003
Station 14	PM2.5	3,578	3,578	0.001	0.008	0.003
Station 15	PM2.5	3,611	3,611	0.001	0.033	0.004

## Attachment D

### **Meteorological Conditions**



